

2027

NINJA® ZX™-4RR ABS

Kawasaki

Let the Good Times Roll®



- LIME GREEN
- SILVER GALAXY



POWER		REAR	
Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Rear Tire	160/60-17
Displacement	399cc	Front Brakes	Dual 290mm semi-floating discs with radial-mount 4-piston monobloc caliper and ABS
Bore x Stroke	57.0 x 39.1mm	Rear Brakes	Single 220mm disc with single-piston caliper and ABS
Compression Ratio	12.3:1	Suspension, front	37mm inverted Showa fork with SFF-BP internals and spring preload adjustability/4.7 in
Maximum Horsepower	56.0 hp ¹ @ 11,500 rpm	Suspension, rear	Horizontal back-link, Showa BFRC lite gas-charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in
Maximum Torque	26.5 lb-ft @ 11,000 rpm	Starting System	TCBI with Digital Advance
Fuel System	DFI® with 34mm throttle valves (4)	DETAILS	
Ignition	TCBI with Digital Advance	Frame Type	Trellis, high-tensile steel
Transmission	6-speed, return shift	Rake/Trail	23.5°/3.8 in
Final Drive	Chain	Overall Length	78.3 in
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Power Modes, Anti-lock Brake System (ABS)	Overall Width	30.1 in
Cooling	Liquid Cooled	Overall Height	43.7 in
Carburetor	Fuel Injection	Ground Clearance	5.3 in
Valve System	16-valve	Seat Height	31.5 in
PERFORMANCE		Estimated Dry Weight	385.8 lb**
Front Suspension / Wheel Travel	37mm inverted Showa fork with SFF-BP internals and spring preload adjustability/4.7 in	Curb Weight	416.6 lb*
Rear Suspension / Wheel Travel	Horizontal back-link, Showa BFRC lite gas-charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in	Fuel Capacity	4.0 gal
Front Tire	120/70-17	Wheelbase	54.3 in
		Special Features	4.3" Full-color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP
		Color Choices	Lime Green, Silver Galaxy
		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.