

NEW 2027

TERYX® H2

Kawasaki

Let the Good Times Roll®

- LIME GREEN
- ICE GRAY



POWER		DETAILS	
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Ground Clearance	16.9 in (max) / 16.1 in (std)
Displacement	999cc	Fuel Capacity	14.8 gal
Maximum Horsepower	250.0 hp ¹ @ 9,000 rpm	Turning Radius	21.3 ft
Maximum Torque	146.3 lb-ft @ 8,800 rpm	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Bore x Stroke	73.4 x 59.0mm	Cargo Bed Load Capacity	300 lb
Compression Ratio	7.8:1	Payload Capacity	732 lb
Fuel System	DFI® with (4) 40mm throttle bodies with dual injection; Kawasaki Supercharger	Seating Capacity	2 bucket seats with 4-point seatbelts
Ignition	TCBI with electronic advance	Lighting	All-LED lighting
Starting System	Electric		
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)		
Final Drive	Selectable 2WD/4WD with locking front differential, shaft		
Engine Braking	Yes		
Electronic Rider Aids	Economical Riding Indicator, Power Modes, Kawasaki TRaction Control (KTRC)		
CAPABILITY		Frame	Ladder type, tubular steel
Front Suspension / Wheel Travel	Double wishbone, FOX 3.0 Internal Bypass shocks, adjustable compression damping and adjustable spring preload/23.2 in	Overall Length	134.1 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 3.0 Internal Bypass Shocks, adjustable compression damping and adjustable spring preload/24.0 in	Overall Width	74.0 in
Front Tires	Maxxis® Carnivore Plus 33 x 10.00R16	Overall Height	72.8 in
Rear Tires	Maxxis® Carnivore Plus 33 x 10.00R16	Estimated Dry Weight	2,085.9 lb* / 2,088.1 lb** CA Model
Wheel Type	16-in aluminum wheels	Curb Weight	2,218.2 lb* / 2,220.4 lb* CA Model
Steering	Electric Power Steering (EPS) / rack-and-pinion	Wheelbase	101.0 in
Front Brakes	270mm dual hydraulic discs with 3-piston calipers	Instruments	Digital speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), Driving Mode (2WD/4WD/4WD+Diff Lock), Power Mode (Full/Mid/Low), Economical Riding Indicator, connected indicator, clock, odometer, dual trip meters, total time, trip time, average speed, engine temperature, intake air temperature, battery voltage, boost pressure, CTV temperature, seatbelt warning lamp, maintenance reminder, oil warning lamp, engine check lamp, engine temperature warning lamp, neutral indicator, reverse indicator, headlight high-beam indicator, parking indicator lamp, battery warning lamp, EPS warning lamp, and CVT belt warning lamp
Rear Brakes	270mm dual hydraulic discs with 2-piston calipers	Additional Features	7-in Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP POWERSPORTS, Skid plates w/ drain holes, ERGO-FIT®, 1 DC outlet, 2 USB ports, 4 cup holders, Additional storage
		Color Choices	Lime Green, Ice Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The TERYX® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki TERYX side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.