



2025

# MULE PRO-FXT™ 1000 LE

**Kawasaki**  
Let the Good Times Roll®



-  ROJO CANDY PERSIMMON
-  GRIS ICE



## POTENCIA

Motor	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas
Cilindrada	999cc
Par motor máximo	61.5 lb-ft @ 4,500 rpm
Diámetro por carrer	92.0 x 75.1mm
Relación de compresión	10.1:1
Sistema de combustible	DFI® with 38mm throttle body
Transmisión	Continuously Variable Transmission (CVT) with (H,L,N,R)
Transmisión final	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Frenado del motor	Yes
Alternator Output (max)	90 amp

## CAPACIDAD

Suspensión delantera / recorrido del neumático	Double wishbone/11.0 in
Suspensión trasera / recorrido del neumático	Double wishbone/10.1 in
Neumáticos delanteros	26 x 9-12, radial
Neumáticos traseros	26 x 11-12, radial
Wheel Type	Alloy
Dirección	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering
Tipo de freno de estacionamiento	Independent, mechanical disc
Frenos delanteros	Dual disc, 2-piston caliper
Frenos traseros	Dual disc, 1-piston caliper

Distancia al suelo	12.6 in (max), 11.6 in (std)
Depósito de combustible	7.9 gal
Radio de giro	16.0 ft
Dimensiones de la plataforma de carga (L x An x Al)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Capacidad de la plataforma de carga	999 lb (3-person)/350 lb (6-person)/348 lb CA Model
Capacidad de carga útil	1,616.3/1,263.5 lb CA Model
Asientos	3-person (1 row), 6 person (2 row)
Capacidad de remolque	2,000 lb
Faros	(2) Halogen headlights, (2) LED headlights

## DETALLES

Largo total	135.8 in
Ancho total	64.0 in
Altura total	80.9 in
Dry Weight	1,839.0/1,841.2 lb** CA Model
Peso en orden de marcha	1,913.9/1,916.1 lb* CA Model
Distancia entre ejes	92.3 in
Instrumental	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Características adicionales	Roof, Additional Front Cup Holders
Colores disponibles	Candy Persimmon Red, Ice Gray
Garantía	Garantía limitada Kawasaki de 3 años

Escanear con cámara para ver videos, características clave y más.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
 \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
 All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.  
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visite [puerto-rico.kawasaki-la.com](http://puerto-rico.kawasaki-la.com) para obtener detalles completos del producto.