

NUEVA 2025

TERYX® KRX4™ 1000 LIFTED EDITION

Kawasaki
Let the Good Times Roll®



LIME GREEN/SUPER BLACK



POTENCIA

| | |
|------------------------|---|
| Motor | 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled |
| Cilindrada | 999cc |
| Par motor máximo | 76.7 lb-ft @ 7,000 rpm |
| Diámetro por carrer | 92.0 x 75.1mm |
| Relación de compresión | 11.5:1 |
| Sistema de combustible | DFI® with (2) 50mm throttle bodies |
| Ignition | TCBI with Electronic Advance |
| Arranque | Electric |
| Transmisión | Automatic CVT with centrifugal clutch (H,L,N,R) |
| Transmisión final | Selectable 2WD/4WD with locking front differential, shaft |
| Frenado del motor | Yes |

| | |
|---|---|
| Radio de giro | 24.0 ft |
| Dimensiones de la plataforma de carga (L x An x Al) | 14.6 x 33.1 x 9.1 in |
| Capacidad de la plataforma de carga | 351 lb |
| Capacidad de carga útil | 1,001 lb |
| Asientos | 4 |
| Capacidad de remolque | N/A |
| Faros | (2) LED headlights, (2) LED taillights, LED stoplight |

CAPACIDAD

| | |
|--|---|
| Suspensión delantera / recorrido del neumático | Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in |
| Suspensión trasera / recorrido del neumático | 4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in |
| Neumáticos delanteros | ITP Cryptid 32 x 10.00R15 6PR |
| Neumáticos traseros | ITP Cryptid 32 x 10.00R15 6PR |
| Dirección | Electric Power Steering (EPS) / rack-and-pinion |
| Frenos delanteros | Dual hydraulic discs with 2-piston calipers |
| Frenos traseros | Dual hydraulic discs with single-piston calipers |
| Distancia al suelo | 14.8 in (max), 14.2 in (std) |
| Depósito de combustible | 10.6 gal |

DETALLES

| | |
|-----------------------------|--|
| Cuadro | Ladder type, tubular steel |
| Largo total | 160.0 in |
| Ancho total | 68.1 in |
| Altura total | 76.6 in |
| Peso en orden de marcha | 2,231.1 lb* / 2,233.3 lb* CA Model |
| Distancia entre ejes | 125.8 in |
| Instrumental | Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp |
| Tipo de rueda | Alloy |
| Características adicionales | Elevated snorkel intakes and CVT exhaust duct, Wide fender flares, Front Bumper, F/R Tow Hooks, Steel skid-plates w/ drain holes, Rear view mirror, WARN® VRX 45-S Powersport Winch |
| Colores disponibles | Lime Green/Super Black |
| Garantía | 6 Month Limited Warranty |

Escanear con cámara para ver videos, características clave y más.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visite puerto-rico.kawasaki-la.com para obtener detalles completos del producto.