





METALLIC SPARK BLACK/GREEN



GRIS METALLIC MATTE DARK/NEGRO METALLIC SPARK



POTENCIA

Motor 4-stroke, 2-cylinder, DOHC, liquid-cooled

Cilindrada 649cc

Diámetro por carrera 83.0 x 60.0mm

Relación de compresión

10.8:1

Maximum Horsepower 67.0 hp1 @ 8,000 rpm

Par motor máximo

48.5 lb-ft @ 6,700 rpm

Sistema de combustible

DFI® with Keihin 36mm throttle bodies

Encendido

TCBI with Electronic Advance

Transmisión

6-speed, return shift

Transmisión final

Sealed chain

Asistencia

electrónica para el piloto Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake System (ABS)

RENDIMIENTO

Suspensión delantera/recorrido del neumático

41mm telescopic fork/4.9 in

Suspensión trasera/ recorrido del neumático Horizontal back-link with adjustable preload, swingarm/5.1 in

Neumático delantero 120/70-17 Neumático trasero 160/60-17

Frenos delanteros Dual 300mm petal-style discs with two-piston calipers

and ABS

Frenos traseros Single 220mm petal-style disc (and ABS)

DETALLES

Tipo de chasis

Angulo de dirección/
Avance

Largo total

Ancho total

Altura del asiento

Distancia al suelo

Trellis, high tensile steel

24.0°/3.9 in

30.9 in

40.9 in

41.9 in

5.1 in

31.1 in

Dry Weight 381.5 lb** (ABS) / 379.3 lb** (non-ABS) 50-State Model

Depósito de 4.0 gal

combustible

Distancia entre ejes 55.5 in

Características especiales

Altura del asiento

Peso en orden de

marcha

4.3" All-digital TFT color Instrumentation, Smartphone Connectivity via RIDEOLOGY THE APP

414.5 lb* (ABS) / 412.3 lb* (non-ABS) 50-State Model

Colores disponibles Metallic Matte Dark Gray/Metallic Spark Black, Metallic

Spark Black/Green

Garantía limitada de 12 meses

Escanear con cámara para ver videos, características clave y más.





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of dryes or already. Persect the environment. The Kawasaki MULETE side is an eff-highway worked, only and is not designed or uniqued or

influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visite puerto-rico.kawasaki-la.com para obtener detalles completos del producto.