

NUEVA 2027

RIDGE® CREW LIFTED EDITION

Kawasaki
Let the Good Times Roll®



 SUNBEAM RED/SUPER BLACK



POTENCIA

Motor	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled
Cilindrada	999cc
Potencia máxima	116.0 hp ¹ @ 8,500 rpm
Par máximo	73.8 lb-ft @ 8,000 rpm
Diámetro x Carrera	73.4 x 59.0mm
Relación de compresión	10.6:1
Sistema de combustible	EFI
Ignition	TCBI with Digital Advance
Arranque	Electric
Transmisión	Continuously Variable Transmission (CVT) with (H,L,N,R)
Transmisión final	Selectable 4WD with locking front/rear differential, shaft
Freno motor	Yes
Salida del alternador (máx.)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

CAPACIDAD

Suspensión delantera/ recorrido del neumático	Long-travel, Double wishbone, KYB shocks with piggyback reservoir, adjustable preload and compression damping/12.7 in
Suspensión trasera/ recorrido del neumático	Long-travel, Double wishbone, KYB shocks with piggyback reservoir, adjustable preload and compression damping/12.7 in
Neumáticos delanteros	ITP Cryptid 30 x 10-14
Neumáticos traseros	ITP Cryptid 30 x 10-14
Wheel Type	14" Aluminum
Dirección	Rack-and-pinion w/ Electric Power Steering (EPS)
Freno delantero	Dual hydraulic 249mm discs with two-piston calipers
Freno trasero	Dual hydraulic 249mm discs with single-piston calipers
Altura libre al suelo	14.2/14.6 in (max preload); 14.2 in CA Model

Capacidad de combustible	12.9 gal
Radio de giro	19.0 ft
Dimensiones del compartimento de carga (LxAxA)	27.6 x 41.5 x 12.2 in
Capacidad de carga del compartimento de carga	1,000/600 lb CA Model
Capacidad de carga útil	1,559 lb
Capacidad de asientos	6-person (2 row), bench seats
Capacidad de remolque	2,500 lb
Luces	All-LED lighting

DETALLES

Cuadro	Ladder type, tubular steel
Longitud total	156.3 in
Anchura total	64.0 in
Altura total	82.9 in
Peso seco estimado	2,282.2/2,284.4 lb** CA Model
Peso en orden de marcha	2,392.4/2,394.6 lb* CA Model
Distancia entre ejes	121.7 in
Instrumentación	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Características adicionales	Elevated snorkel intakes and CVT exhaust duct, Raised fender flares, Brush guards, Cargo bed storage compartments, High-Density Polyethylene (HDPE) skid plates w/ drain holes, Rear view mirror, 4,500-lb winch with synthetic rope, Adjustable driver's seat, ERGO-FIT®, 8-in full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible
Opciones de color	Sunbeam Red/Super Black
Garantía	Kawasaki STRONG 3-Year Limited Warranty

Escanear con
cámara para ver
videos, característi-
cas clave y más.



*El peso en orden de marcha del vehículo incluye todos los materiales y fluidos necesarios para su correcto funcionamiento, el depósito de combustible lleno (más del 90 por ciento de su capacidad) y el kit de herramientas (si se suministra).
** El peso en seco del vehículo excluye todos los materiales y fluidos necesarios para su correcto funcionamiento, el depósito de combustible lleno (más del 90 por ciento de su capacidad) y el kit de herramientas (si se suministra).
¹Los CV de este vehículo se han medido según la norma ISO 4106. Este estándar ISO mide los CV de manera diferente a los estándares SAE mediante los cuales se mide la potencia de muchos automóviles y, como resultado, la medición de CV a la que se hace referencia puede ser mayor que si se midiera según un estándar SAE.
Especificaciones sujetas a cambios. Visite puerto-rico.kawasaki-la.com para obtener detalles completos del producto.